

1. (Currently Amended) A differential radio comprising:
  - a differential antenna having an input and an output;
  - a differential duplexer including film bulk acoustic resonators, generating two receiving signals and receiving two transmitting signals, electrically connected to the input and output of the differential antenna;
  - a differential low noise amplifier, receiving the two receiving signals, generating two LNA signals, including,
    - an input matching network having a differential input and a first and second IMN output;
    - a first field effect transistor (FET), having a gate connected to the first IMN output;
    - a first capacitor, connected to the drain of the first FET;
    - a second FET, having a gate connected to the first capacitor;
    - a third FET, having a source connected to the source of the second FET [at a first node];
    - an output matching (OMN), having a first input connecting to the drain of the second FET and a second input connecting to the drain of the third FET;
    - a first inductor connecting between the source of the second FET and ground;
    - a second capacitor connected to the gate of the third FET;
    - a fourth FET having a drain connected to the second capacitor, a gate connected to the second IMN output, a source connected to the source of the first FET; and
    - a second inductor connects between the source of the first FET and ground;
  - a first differential filter receiving the two LNA signals and generating a first differential filter signal;
  - a first differential mixer receiving the first differential signal and generating a first differential mixer output signal;
  - a signal conditioning circuit, receiving the first differential mixer output signal, generating a conditioned differential signal;

a second differential mixer, receiving the conditioned differential signal, generating a second differential mixer output signal;  
a second differential filter, receiving the second differential mixer output signal, generating a second differential filter signal; and  
a differential power amplifier receiving the second differential filter signal and generating the two transmitting signals.

2-6. (Cancelled)

7. (Currently Amended) A differential radio as in claim [[5]] 1, wherein the differential antenna is incorporated into a printed circuit board.